Long Run PS Plate ECOO-PS



Model	ECOO-PS
Plate Type	Positive PS Plate
Application	commercial and newspaper printing
Substrate	Electro chemically Grained and Anodized lithographic Aluminum
Gauge	0.15, 0.30(mm)
Maximum short grain width	Maximum width 1280 mm
Power of light	3000 – 5000 w
Length of Run	Unbaked: 50000 to 100,000 impressions
	Baked: Over 100,000 impressions
Processor	All brands or Manual
Aluminum	Standard 1050 Alloy
Developing time	20-30 sec
Spectral Sensitivity	320 – 405 nm
Resolution	2-98% @ 200LPI
Image Color	Green
Developer	Any positive plate developer or our own developer
Processing temperature	20-25℃
Processing Speed	0.80 – 1.20 m/min
safelight	Handle under yellow safe light(UV free)
Shelf life	12 months under recommended storage conditions
Packaging	Available in all standard formats, including bulk packaging options such as APL packaging
Storage and handing	Stored in a cool and dry environment, away from excessive cold, heat and humidity



Hangzhou EcooGraphix Digital Technology Co, Ltd.

Add: Room 708, Tianheng Building, No.1509, Binsheng Rd, Binjiang District, Hangzhou, China

Tel: 0086 571-87391001 Fax:0086 0571-87391001

E-mail:info@ecoographix.com Website: www.ecoographix.com